

Fusil® K805L

Silica Matting Agent

Fusil® K805L is an amorphous silica treated with a special surfactant, fine particle size and delicate soft-touch, which meets the requirements of customers for the increasingly high soft-touch of the surface of the paint film. It can replace TOSOH E-1011.

Characteristic physico-chemical data

Test Item	Unit	Value
SiO ₂ %(dry)	%	≥98%
D50 um	um	3-5
Heating Loss	%	≤3.5
Ignition Loss	%	≤5.0
DBP	g/100g	≥250
Surface Treatment	/	Yes

Properties

- Excellent Transparency
- Good Dispersion, No Hard Precipitation
- Delicate soft-touch
- Less Influence on System Viscosity

Packing and storage

- Packaged in multiple layer Kraft paper, 10kg per bag
- Product more than 24 months old should be tested

for moisture content before use in order to make certain that it is still suitable for the intended application.

Applications

- UV&PU System Casing Coating
- Elastic Paint
- Other Systems with High soft-touch and Transparency Requirements

Safety & Handling

Information concerning the safety of this product is listed in the corresponding Safety Data Sheet, which will be sent with the first delivery or upon updating. Such information is also available from Fusil, Product Safety Department, EMAIL info@fuchangchem.com or can check from our homepage www.fuchangchem.com. We recommend to read carefully the safety data sheet

Service

Email: info@fuchangchem.com

Tel: 0086-411-83607405

Website: www.fuchangchem.com