

Fusil[®] K808

Silica Matting Agent

Fusil[®] K808 is a gel silica produced by a special process. It has high extinction efficiency and good dispersibility. It is suitable for systems with special requirements on system viscosity.

Characteristic physico-chemical data

Test Item	Unit	Value
SiO ₂ %(dry)	%	≥98%
D50 um	um	5-7
Heating Loss	%	≤6
Ignition Loss	%	≤5
DBP	g/100g	220-250
Surface Treatment	/	No

Properties

- Excellent dispersion
- Good Matting Properties
- Lesser influence for system viscosity

Packing and storage

- Packaged in multiple layer Kraft paper, 10kg per bag
- Product more than 24 months old should be tested for moisture content before use in order to make

certain that it is still suitable for the intended application.

Applications

It is recommended for UV wood floor coatings, coil coatings and ink those have special request on viscosity. Low-thixotropic industrial paint.

Safety & Handling

Information concerning the safety of this product is listed in the corresponding Safety Data Sheet, which will be sent with the first delivery or upon updating. Such information is also available from Fusil, Product Safety Department, EMAIL info@fuchangchem.com or can check from our homepage www.fuchangchem.com. We recommend to read carefully the safety data sheet

Service

Email: info@fuchangchem.com

Tel: 0086-411-83607405

Website: www.fuchangchem.com