

Fusil<sup>®</sup> K801

## Silica Matting Agent

Fusil K801 is a specially processed gel silica. The extinction efficiency is particularly good, neatly arranged, excellent dispersion. It can replace Grace Syloid ED-3

## Characteristic physico-chemical data

| Test Item               | Unit   | Value |
|-------------------------|--------|-------|
| SiO <sub>2</sub> %(dry) | %      | ≥99   |
| D50 um                  | um     | 6.7   |
| Pore Volume             | ml/g   | 1.8   |
| Heating Loss            | %      | ≤3.5  |
| Ignition Loss           | %      | ≤5    |
| DBP                     | g/100g | ≥290  |
| Surface Treatment       | /      | No    |

## Properties

- Extremely high matting property
- Good dispersion

## Packing and storage

- Packaged in multiple layer Kraft paper, 10kg per bag
- Product more than 24 months old should be tested for moisture content before use in order to make

certain that it is still suitable for the intended application.

## Applications

- Mainly used in wood paint, furniture paint systems, coil coatings, and general industrial paints.

## Safety &amp; Handling

Information concerning the safety of this product is listed in the corresponding Safety Data Sheet, which will be sent with the first delivery or upon updating. Such information is also available from Fusil, Product Safety Department, EMAIL [info@fuchangchem.com](mailto:info@fuchangchem.com) or can check from our homepage [www.fuchangchem.com](http://www.fuchangchem.com). We recommend to read carefully the safety data sheet

## Service

Email: [info@fuchangchem.com](mailto:info@fuchangchem.com)

Tel: 0086-411-83607405

Website: [www.fuchangchem.com](http://www.fuchangchem.com)