

Fusil® K807

Silica Matting Agent

Fusil® K807 is a specially designed precipitation method silica, organic treatment, easy to disperse, good matting, increase slip, good suspension, can be applied to a variety of coating systems. Can replace OK520.

Characteristic physico-chemical data

Test Item	Unit	Value
SiO ₂ %(dry)	%	≥98
D50 um	um	7-9
Heating Loss	%	≤6
Ignition Loss	%	≤12
DBP	g/100g	≥350
Surface Treatment	/	Yes

Properties

- Excellent suspension
- Excellent matting effect, easy to disperse
- High transparency, increased slip resistance
- Chemical resistance, water resistance.

Packing and storage

- Packaged in multiple layer Kraft paper, 10kg per bag
- Product more than 24 months old should be tested for moisture content before use in order to make

certain that it is still suitable for the intended application.

Applications

It is recommended for high matting request of water-based paint and wood paint. Baking paint, two-component polyurethane paint, plastic paint.

Safety & Handling

Information concerning the safety of this product is listed in the corresponding Safety Data Sheet, which will be sent with the first delivery or upon updating. Such information is also available from Fusil, Product Safety Department, EMAIL info@fuchangchem.com or can check from our homepage www.fuchangchem.com. We recommend to read carefully the safety data sheet

Service

Email: info@fuchangchem.com

Tel: 0086-411-83607405

Website: www.fuchangchem.com