

## Precipitated Silica

Fusil<sup>®</sup> SDA720 is precipitated silica for feed grade, as the carrier for feed additives. It is white powder with high purity and excellent fluidity.

### Characteristic physico-chemical data

Item	Specification	Standard
BET (m <sup>2</sup> /g)	160-180	GB/T 10722
SiO <sub>2</sub> % (dry basis)	≥98	HG/T 3062
Heat Loss %	≤8.0	HG/T 3065
Ignition Loss (Dry Basis) %	≤7.0	HG/T 3066
Soluble Salts % (in form of Na <sub>2</sub> SO <sub>4</sub> )	≤3.0	HG/T 3748
PH(10% Solution)	6.0~7.5	HG/T 3067
DBP (cm <sup>3</sup> /g)	2.5-3.5	HG/T 2404
Heavy Metal (in form of Pb) %	≤0.003	IEC62321-5

### Applications

- Carrier for feed additives

### Packing and storage

- Packaged in multiple layer Kraft paper, 15kg per bag.
- Stored in aeration-drying storage areas for protecting the material from volatile substance.
- Should be used within 2 years after production.

### Properties

- High moisture adsorption
- Flow promotion
- Anti-caking
- It is excellent carrier for feed flavoring agent, mould inhibitor, anti-acid agent, antioxidant, silicon-type choline chloride, allicin, animal medicine, cosmetics etc.

### Safety & Handling

Information concerning the safety of this product is listed in the corresponding Safety Data Sheet, which will be sent with the first delivery or upon updating. Such information is also available from Fuchang Chemical, Product Safety Department, E-MAIL [info@fuchangchem.com](mailto:info@fuchangchem.com) or can check from our homepage [www.fuchangchem.com](http://www.fuchangchem.com). We recommend to read carefully the safety data sheet prior to the use of our product.

### Transportation

- 20'GP: 6.0Mt, 10 pallets, 600KG/pallet.
- 40'HQ: 15.84Mt, 22 pallets, 720KG/pallet.

### Service

Email: [info@fuchangchem.com](mailto:info@fuchangchem.com)

Tel: 0086-411-83607405

Website: [www.fuchangchem.com](http://www.fuchangchem.com)